STROEKS et al Serial No. 10/582,909 January 8, 2010

AMENDMENT TO THE CLAIMS:

The following claim set replaces all prior versions, and listings, of claims in the application:

- (previously presented) Oxygen scavenging composition comprising a
 polycondensate, a copolymer comprising polyoxy-1,2-propanediyl segments and
 polymer segments, and an oxidation catalyst, wherein the copolymer is the
 copolymerisation reaction product of the corresponding monomers in the
 presence of functionalised polyoxy-1,2-propanediyl segments.
- (original) Oxygen scavenging composition according to claim 1, wherein the polymer segments are polyamide or polyester.
- (previously presented) Oxygen scavenging composition according to claim 1, wherein the polycondensate is (co)polyamide or (co)polyester or mixtures thereof.
- (currently amended) Oxygen scavenging composition according to claim 1, wherein the polycondensate and the polymer segments are of the same-type both polyamides or polyesters.
- (previously presented) Oxygen scavenging composition according to claim 1, wherein the amount of polyoxy-1,2-propanediyl segments is from 0.5 to 50 wt% with respect to the composition.
- (previously presented) Oxygen scavenging composition according to claim 5, wherein said amount of polyoxy-1,2-propanediyl segments is in the range from 1 to 30 wt%.

STROEKS et al Serial No. 10/582,909 January 8, 2010

- (previously presented) Oxygen scavenging composition according to claim 1
 wherein the polyoxy-1,2-propanediyl segments are present as conglomerates
 and at most 25% of the conglomerates have a size above 500nm.
- (previously presented) Oxygen scavenging composition according to claim 1, wherein the oxidation catalyst is a transition metal salt or complex.
- (currently amended) Oxygen scavenging composition according to claim 1
 having an oxygen barrier lower than 0.3 cc.mm/(m²-day-atm) when measured
 according to ASTM standard D3985-02 under dry conditions on a film having a
 thickness of 60 um.
- (currently amended) Oxygen scavenging composition according to claim 9, having an oxygen barrier lower than 0.1 cc.mm/(m²-day-atm) when measured according to ASTM-standard D3985 under dry conditions on a film having a thickness of 60 µm.
- 11. (withdrawn) Process for preparing an oxygen scavenging composition comprising a polycondensate, a copolymer comprising polyoxy-1,2-propanediyl segments and polymer segments, and an oxidation catalyst, the process comprising melt-mixing a polycondensate with a copolymer that is the copolymerization reaction product of the corresponding monomers constituting the polymer segments in the presence of functionalised polyoxy-1,2-propanediyl segments, and adding an oxidation catalyst to the mixture.
- 12. (withdrawn) Process for preparing an oxygen scavenging composition comprising a polycondensate, a copolymer comprising polyoxy-1,2-propanediyl segments and polymer segments, and an oxidation catalyst, the process comprising preparing a copolymer by copolymerising the corresponding monomers constituting the polymer segments in the presence of functionalised

STROEKS et al Serial No. 10/582,909 January 8. 2010

- polycondensate, and adding an oxidation catalyst to the mixture.
- (withdrawn) An oxygen scavenging object which comprises an oxygen scavenging composition according to claim 1.
- 14. (withdrawn) An oxygen scavenging object according to claim 13, wherein the object is a container for food, drink or feed packaging such as a film, a bottle, a vessel or a wrap.
- 15. (withdrawn) An oxygen scavenging object according to claim 13, wherein the object is a multilayer object in which a layer of the oxygen scavenging composition is sandwiched between two layers of another material.
- 16. (withdrawn) Object, having at least one surface that is to be exposed to an oxygen containing environment, and comprising a layer containing the composition according to claim 1, in which conglomerates of the polyoxy-1,2-propanediyl segments are present, of which conglomerates at least 90% has a dimension in at least one spatial direction that is larger than a dimension in at least one other spatial direction by a factor of at least 1.3, and in which said larger dimension extends in a direction parallel to the at least one surface.
- (withdrawn) Object according to claim 16, wherein the dimension of at most 25% of the conglomerates in a direction perpendicular to the at least one surface is less than 350 nm.
- (withdrawn) Object according to claim 16, wherein the object is a container for food, drink or feed packaging such as a film, a bottle, a vessel or a wrap.

STROEKS et al Serial No. 10/582,909 January 8, 2010

 (withdrawn) Object according to claim 16, wherein the object is a multilayer object in which a layer of the oxygen scavenging composition is sandwiched between two layers of another material.